



RK710X1

Upright Cooler GN2/1

Product Features

- Stainless steel cabinet
- Controller with Bluetooth and NFC connectivity
- Ventilated cooling
- Reversible solid door
- Self-closing door with a 105 degree stop
- Adjustable shelves GN2/1
- Maintenance free condenser
- Strong wheels
- Lock
- Accessory - Pedal for opening door (right or left hinged)

1-door stainless steel cooler for professional kitchens

The RK710X1 is an energy-efficient cooler for professional settings. It has a 36% lower energy consumption compared to the previous RK710 model. This upright cooler is made from durable SS304 stainless steel to ensure that it can withstand the conditions of a busy kitchen. It comes with adjustable GN2/1 shelves and the door has a 105 degree stop for easy access and loading. A pedal for opening the door is also available as an accessory. The cabinet is equipped with strong wheels, which come in handy in terms of cleaning. It has an efficient ventilated cooling system to ensure that content stays fresh, and the temperature is easy to set on the digital controller. The controller has NFC connectivity and Bluetooth. This means you can keep an eye on the temperature and humidity of the cabinet via an app, and you can export data for easy reporting.

Measures and Content

Temperature Range	°C	-2 to +8
Climate Class		5
Gross / Net Weight	kg	143 / 134
Gross / Net Volume	l	559 / 393

Design and Material

Door No & Type		1 hinged self-closing solid door
Shelves No & Type		3 wire shelves grey
Shelf Color		Grey
Max load on Shelves	kg/m ²	25
Castors		4 castors
Exterior Finish		SS304
Interior Finish		SS304
Interior Light		LED
Lock		Yes

Cooling and Functions

Type of Controller		Electronic
Type of Cooling		Ventilated
Type of Defrost		Automatic-Off Cycle
Refrigerant		R600a
Refrigerant Charge	g	140
Thermometer		Yes

Power and Consumption


Energy Class		A
Energy Consumption	kWh/24h	0.75
Annual Energy Cons.	kWh/year	277
Input Power	W	100
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	46

Dimensions

Internal Dimension (WxDxH)	mm	533 x 700 x 1501
External Dimension (WxDxH)	mm	740 x 875 x 2090
Packed Dimension (WxDxH)	mm	760 x 905 x 2150
40ft Container Load	pcs	39



Adjustable shelves



Castors with and without brake